

DULCONNEX Gateway

Secure and reliable provision of IIoT data



The DULCONNEX Gateway safely and reliably transfers the data of all products supported as standard to the DULCONNEX Cloud

Technical Details

- Compact “embedded” design
- Industrial quality housing with IP65
- Communication interfaces to ProMinent products: Ethernet or CANopen
- Communication interface to the DULCONNEX Cloud: Wi-Fi
- Frequency and transmission output: 2.4 GHz, 100 mW
- Power supply: 100-230 VAC \pm 10 %, 50/60 Hz
- Power consumption: 50-30 mA, 6 W
- CE, FCC and ANATEL certification



DULCONNEX Gateway

Secure and reliable provision of IIoT data

	Suitable for system types	Order no.
DULCONNEX Gateway AGIb	AEGIS II	1098723
DULCONNEX Gateway DACb	DULCOMETER diaLog DACb	1098756
DULCONNEX Gateway pumps and I/O modules	gamma/ X, gamma/ XL, delta, DULCOFLEX DF4a, DULCOFLEX DFXa, DULCOFLEX DFYa, I- and M-modules (DULCOMARIN II), Frenzel+Berg modules (CIO50, CIO57, CIO58, CIO60, CIO300), Sigma X	1105889
DULCONNEX Gateway UVCb, CDLb	DULCODES LP/MP, chlorine dioxide systems Bello Zon CDLb	1098757
DULCONNEX API	DULCONNEX BLE gateway DULCOLEVEL	1136479